

1600XD4 DIESEL 4X4

User-Selectable 4WD

22 hp, 1,007cc 3-Cylinder OHV Diesel Engine

Four-Wheel Independent Suspension

22HP
DIESEL

1325^{lb}_{MAX}
LOAD

1300^{lb}_{MAX}
TOW



Features and specifications of the vehicles are subject to change without notice.
Vehicle as photographed may include options not included on base model.

CUSHMAN®



CUSHMAN
LET'S WORK.

The Muscle to Haul Equipment and Your Crew Efficiently.

Designed to move more people around a jobsite without compromising any power or payload, the Cushman® 1600XD4 can seat four crew members comfortably. The Cushman 1600XD4 comes standard with two rows of bench seating. The vehicle has a 1,325-pound payload capacity and can tow up to 1,300 pounds.

This powerful 4x4 diesel, combines four-wheel-drive capability with a powerful 22 hp, 1,007cc three-cylinder OHV diesel engine. Its performance is further enhanced by an automatic, continuously variable transmission (CVT) with low- and high-gear ratios, a user-selectable locking rear differential which can be engaged in both 2WD- and 4WD-operation, and four-wheel independent suspension.

When productivity is a premium to your crew, the Cushman 1600XD4 is the choice.



Factory Installed Options & Field Accessories

- Hard Cab
- Skid Plates
- Heater/Defroster
- Fog & Working Lights
- Bed Extension
- Electric or Hydraulic Dump Kits
- Front Receiver
- Mud Tires
- Turf Tires

1600XD4 DIESEL 4X4

DIMENSIONS	
Overall Length	144.5 in (367.3 cm)
Overall Width	60.7 in (154.2 cm)
Overall Height	76.4 in (194.1 cm)
Wheel Base	108.7 in (276.1 cm)
Front Wheel Track	49.7 in (126.2 cm)
Rear Wheel Track	48.3 in (122.7 cm)
Ground Clearance	12.0 in (30.5 cm)
Cargo Box Width (inside)	56.2 in (142.7 cm)
Cargo Box Length (inside)	38.5 in (98.0 cm)
Cargo Box Depth (inside)	11.5 in (29.2 cm)
POWER	
Engine	3Cyl., In-line Vertical, Water-Cooled
Horsepower (kW)	22 hp (16.4 kW)
Electrical System	Starter / Alternator
Batteries (Qty, Type)	One, 12 Volt (690 CCA @ 0° F)
Key or Pedal Start	Key
Air Cleaner	Dry-Cyclone Type
Lubrication	Pressurized
Oil Filter	Spin-On
Cooling System	Liquid Cooled
Fuel Capacity	7.4 Gallon (28.0 L) tank
Drive Train	Belt, Continuously Variable Transmission (CVT)
Transaxle	Differential Lock (Limited Slip Device on Front Axle)
Gear Selection	Forward H - Forward L - Neutral - Reverse
Rear Axle Ratio	20:1 (Low), 13.5:1 (High), 8.5:1 (Reverse)
PERFORMANCE	
Seating Capacity & Style	4-Person. Bench
Curb Weight	1,852 lbs (840 kg)
Bed Load Capacity	660 lbs (300 kg)
Vehicle Load Capacity	1325 lbs (600 kg)
Outside Clearance Circle	35.4 ft (10.7 m)
Speed - High (level ground)	25 mph (40.2 kph)
Speed - Low (level ground)	10.6 mph (17.0 kph)
Speed (reverse)	15.6 mph (25.0 kph)
Towing Capacity	1,300 lbs (589 kg)
STEERING & SUSPENSION	
Steering	Hydraulic Power Steering
Front Suspension	Independent, MacPherson Strut Type
Rear Suspension	Independent, Double A-Arm Wishbone Type
Parking Brake	Single Point Engagement
Front & Rear Tires	All-Terrain 25 x 10 - 12 in
FRAME & COLOR	
Frame	Welded Steel with powder-coat protection
Front Body & Finish	Injection Molded Body
Rear Body & Finish	Steel Cargo Bed
Standard Color	Patriot Blue

**DEALER
LOGO**

[CUSTOMIZABLE DEALER NAME HERE]

[Customizable Dealer Address]
[Dealer City], [Dealer State], [Dealer ZIP]
[Dealer Web Address]